




PRODUCT DESCRIPTION

Transform ordinary walls into custom architectural features with our Fabric-Wrapped Acoustic Panel Shapes. Available in circles, hexagons, and triangles, these versatile acoustic panels combine modern design with effective sound control to create quieter, more comfortable environments in offices, schools, healthcare facilities, hospitality spaces, churches, and other commercial interiors.

Each panel features a 1" recyclable polyester acoustic core wrapped in your choice of premium acoustical fabrics and delivers a 0.75 NRC to help reduce echo, absorb unwanted sound, and improve speech clarity.

Available in multiple sizes and three distinctive geometric shapes, these panels can be installed individually or combined to create unique wall displays, honeycomb patterns, or custom layouts that reflect your project's aesthetic.

Choose from four fabric collections, including industry-leading Guilford of Maine fabrics, to coordinate with your interior design. Lightweight and easy to install, Fabric-Wrapped Acoustic Shapes offer endless design possibilities without the cost and lead time of custom fabrication.





PRODUCT FEATURES

High-Performance Sound Absorption

The 1 inch polyester acoustic core features a 0.75 NRC which helps reduce reverberation, minimize distracting noise, and improve speech intelligibility in open or high-traffic environments.

Multiple Shapes, Endless Possibilities

Available in circles, hexagons, and triangles and offered in multiple sizes, these acoustic panels can be mixed and matched to create custom wall installations ranging from simple statement pieces to large-scale architectural features.

Sustainable & Recyclable Construction

Manufactured with a durable 100% recyclable polyester core, these clouds offer an environmentally responsible acoustic solution without sacrificing performance or appearance.

Class A Fire Rated

Tested for safety and performance, the clouds meet Class A fire rating requirements, making them suitable for a wide range of commercial, educational, hospitality, and public spaces.

Manufactured in the USA

Proudly manufactured in the United States with quality craftsmanship and attention to detail.

SOUND ABSORPTION AT VARIOUS FREQUENCIES


Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
Polyester 1" (.75 NRC)	.06	.34	.68	.93	.98	.97

POLYESTER CORE: TECHNICAL INFORMATION AND SPECIFICATIONS


Core	Polyester
Core Density	5 pounds per cubic foot (5 PCF)
Design	Frameless
Flammability Rating	Class A
Manufacturing Tolerance	+/- 1/4" from centerline
Architectural Product Reference	Sound Absorbing Wall Unit
Fabric Material	Polyester Blend




CLASSIC 700 SERIES FABRICS




CLASSIC
BLACK




CLASSIC
BLUESTONE
SLATE




CLASSIC LIGHT
OAT



CLASSIC
PATINA GREY



CLASSIC PURE
WHITE




CLASSIC
TAN


ACOUSTICS AMERICA FABRICS




SEA FOAM
WHITE




FULL MOON
SILVER




INDUSTRIAL
STEEL GREY



NATURAL
STONE GREY




FREEDOM
GREY




MIDNIGHT
BLACK




AMERICAN
WALNUT




DELICIOUS
APPLE RED




FALL HARVEST
ORANGE




HEARTLAND
WHEAT



BARNWOOD
GREY




SAND SILVER




MOJAVE TAN




COUNTRY
CREAM




SAN JOAQUIN
OLIVE




SILENT
EVERGREEN



GREAT LAKES
BLUE



WESTERN SKY
BLUE



WILD PLUM




GUILFORD OF MAINE ANCHORAGE-2335 FABRICS




WHITE #2664



BIRCH #2129



SLATE #2017



WOLF #2027



GRAPHITE
#2079



ONYX #2016

Specifications

Content	65% pre-consumer recycled polyester 35% post-consumer recycled polyester
Weight	2334 - 13.1 ± 1.0 oz./lin. yd 2335 - 15.0 ± 1.0 oz./lin. yd
Width	2334 - 54" min. useable 2335 - 66" min. useable
Repeat	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- Please specify when ordering whether 54" or 66" width is needed. Dye lots may vary. Differences may also occur between corresponding colors of Anchorage 2335 and Open House 2334.

Proudly woven in North America supporting our local communities.

Sustainability

100% recycled and recyclable

Performance



Colorfastness to light (AATCC 16.3 Option 3)
Grade 4 min. at 40 hours



Colorfastness to crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

Breaking Strength (ASTM D5034)
275 lbf min. warp and fill



Seam Slippage (ASTM D4034)
50 lbf min. warp and fill

Pilling Resistance (ASTM D3511)
Class 4 min.



Flammability
CA Technical Bulletin 117-2013 Section 1
ASTM E84 Class I or A



Abrasion (ASTM D4157)
250,000 double rubs min. cotton duck

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 85%



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Certification Marks owned by the Association for Contract Textiles, Inc.



GUILFORD OF MAINE FR701-2100 FABRICS



WHITE #224




EGGSHELL
#144




BONE #748




WHEAT #130




SILVER PAPIER
#538




SILVER
NEUTRAL #406




GREY MIX #238




STEEL GREY
#471



FLANNEL #795



MEDIUM GREY
#298



WEDGEWOOD
#150



BLACK #408

Specifications

Content	100% post-consumer recycled polyester
Weight	16.0 ± 0.5 oz./lin. yd
Width	66" min. useable
Repeat	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Bleach Cleanable - May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

Application testing of this product is recommended. Colors may vary between dye lots. This is a non-directional fabric.

Proudly woven in North America supporting our local communities.

Sustainability

100% recycled and recyclable

Performance



Colorfastness to light (AATCC 16.3 Option 3)
Grade 4 min. at 40 hours



Colorfastness to crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034)
150 lbf min. warp and fill



Flammability
ASTM E84 Class I or A

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 95%

For more detailed results, please consult our website.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

Certification Marks owned by the Association for Contract Textiles, Inc.